

SAFETY DATA SHEET NOROX KP-100

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NOROX KP-100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : Dalian Hefu Trading Co., LTD
Room 1003 Yihua Building, NO 215 Huanghai Xisi Road
Dalian F.T.Z., Liaoning, China

E-mail address of person
responsible for the SDS : Great@dlwawoo.com
tangaizhang@hefuchem.com

1.4 Emergency telephone number : 0086-411-39552935

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--------------------------------|--|
| Organic peroxides, Type D | H242: Heating may cause a fire. |
| Acute toxicity, Category 4 | H302: Harmful if swallowed. |
| Acute toxicity, Category 4 | H332: Harmful if inhaled. |
| Skin corrosion, Category 1B | H314: Causes severe skin burns and eye damage. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H242 Heating may cause a fire.
H302 + H332 Harmful if swallowed or if inhaled
H314 Causes severe skin burns and eye damage.

Precautionary statements :

Prevention:

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.
P233 Keep container tightly closed.
P235 Keep cool.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P262 Do not get in eyes, on skin, or on clothing.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P315 Get immediate medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

2-Butanone, peroxide (CAS-No. 1338-23-4)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxide
Liquid mixture

Hazardous components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|----------------------|--|---|--------------------------|
| 2-Butanone, peroxide | 1338-23-4 215-661-2 | Org. Perox. D; H242 Acute Tox. 4; H302 | >= 30 - < 35 |

| | | | |
|--------------------------|--|--|------------------|
| | 01-2119514691-43 | Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 | |
| Hydrogen peroxide | 7722-84-1 231-765-0 01-2119485845-22 | Ox. Liq. 1; H271 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Chronic 3; H412 | $\geq 1 - < 2.5$ |
| 2-Methyl-2,4-pentanediol | 107-41-5 203-489-0 01-2119539582-35 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 | $\geq 1 - < 3$ |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Call a physician immediately.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Call a physician immediately.
If breathed in, move person into fresh air.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Call a physician immediately.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed or if inhaled
Causes serious eye damage.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
The product burns violently.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
The product will float on water and can be reignited on surface water.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.
Remove undamaged containers from fire area if it is safe to do so.
Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Follow safe handling advice and personal protective equipment recommendations.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
Clear spills immediately.
Suppress (knock down) gases/vapours/mists with a water spray jet.
To clean the floor and all objects contaminated by this material, use plenty of water.
Soak up with inert absorbent material.
Isolate waste and do not reuse.
Non-sparking tools should be used.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

- Advice on safe handling : Do not swallow.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
Avoid formation of aerosol.
Take precautionary measures against static discharges.
Never return any product to the container from which it was originally removed.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Protect from contamination.
- Advice on protection against fire and explosion : Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from combustible material.
- Hygiene measures : Keep away from food and drink. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from strong acids, bases, heavy metal salts and other reducing substances.
- Recommended storage temperature : < 30 °C
- Other data : No decomposition if stored normally.

7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parameters | Basis |
|------------|---------|------------------|--------------------|-------|
|------------|---------|------------------|--------------------|-------|

| | | of exposure) | | |
|--------------------------|--------------------------|--------------|----------------------------------|---------|
| dimethyl phthalate | Dimethyl phthalate | TWA | 5 mg/m ³ | GB EH40 |
| | | STEL | 10 mg/m ³ | GB EH40 |
| 2-Butanone, peroxide | 2-Butanone, peroxide | STEL | 0.2 ppm 1.5 mg/m ³ | GB EH40 |
| Hydrogen peroxide | Hydrogen peroxide | TWA | 1 ppm 1.4 mg/m ³ | GB EH40 |
| | | STEL | 2 ppm 2.8 mg/m ³ | GB EH40 |
| 2-Methyl-2,4-pentanediol | 2-methylpentane-2,4-diol | TWA | 25 ppm 123 mg/m ³ | GB EH40 |
| | | STEL | 25 ppm 123 mg/m ³ | GB EH40 |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------------|---------|-----------------|----------------------------|------------------------|
| 2-Butanone, peroxide | Workers | Inhalation | Long-term systemic effects | 2.35 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 1.33 mg/kg bw/day |
| | Workers | Inhalation | Acute systemic effects | 7.05 mg/m ³ |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------------|---------------------------|---------------|
| 2-Butanone, peroxide | Fresh water | 0.0056 mg/l |
| | Marine water | 0.00056 mg/l |
| | Intermittent use/release | 0.056 mg/l |
| | Sewage treatment plant | 1.2 mg/l |
| | Fresh water sediment | 0.0876 mg/kg |
| | Marine sediment | 0.00876 mg/kg |
| | Soil | 0.0142 mg/kg |

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.
Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

| | | |
|--------------------------|---|---|
| Skin and body protection | : | Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. |
| Respiratory protection | : | In the case of dust or aerosol formation use respirator with an approved filter. |
| Filter type | : | ABEK-filter |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | |
|--|---|--|
| Appearance | : | liquid |
| Colour | : | colourless, clear |
| Odour | : | mint-like |
| pH | : | No data available |
| Melting point/range | : | No data available |
| Boiling point/boiling range | : | Decomposition: Decomposes below the boiling point. |
| Flash point | : | > 80 °C Method: ISO 3679 |
| Flammability (solid, gas) | : | Not applicable |
| Upper explosion limit | : | No data available |
| Lower explosion limit | : | No data available |
| Vapour pressure | : | No data available |
| Density | : | 1.12 g/cm ³ (20 °C) |
| Solubility(ies) | | |
| Water solubility | : | slightly soluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Viscosity | | |

| | | |
|----------------------|---|--|
| Viscosity, dynamic | : | 19 - 23 mPa.s |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. Organic peroxide |

9.2 Other information

| | | |
|--|---|--|
| Self-Accelerating decomposition temperature (SADT) | : | $\geq 60\text{ }^{\circ}\text{C}$ Method: UN-Test H.4 SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction. |
|--|---|--|

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

| | | |
|---------------------|---|--|
| Hazardous reactions | : | Vapours may form explosive mixture with air. |
|---------------------|---|--|

10.4 Conditions to avoid

| | | |
|---------------------|---|---|
| Conditions to avoid | : | Protect from contamination. Contact with incompatible substances can cause decomposition at or below SADT. Heat, flames and sparks. Avoid confinement. |
|---------------------|---|---|

10.5 Incompatible materials

| | | |
|--------------------|---|---|
| Materials to avoid | : | Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents |
|--------------------|---|---|

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled

Product:

Acute oral toxicity : Acute toxicity estimate: 1,406 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg
Method: Expert judgement

Hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 6,500 mg/kg

2-Methyl-2,4-pentanediol:

Acute oral toxicity : LD0 (Rat): > 4,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 7,892 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: Extremely corrosive and destructive to tissue.

Components:

2-Butanone, peroxide:

Species: Rabbit

Result: Causes burns.

Hydrogen peroxide:

Result: Corrosive after 3 minutes or less of exposure

2-Methyl-2,4-pentanediol:

Species: Rabbit

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

2-Butanone, peroxide:

Result: Irreversible effects on the eye

Hydrogen peroxide:

Result: Irreversible effects on the eye

2-Methyl-2,4-pentanediol:

Species: Rabbit

Result: irritating

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

2-Butanone, peroxide:

Species: Guinea pig

Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

Assessment: Harmful if swallowed., Harmful if inhaled.

2-Methyl-2,4-pentanediol:

Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative
: Method: OECD Test Guideline 471
Result: negative
: Method: OECD Test Guideline 476
Result: negative

Hydrogen peroxide:

Genotoxicity in vitro : Test Type: Ames test
Result: negative
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Result: negative

2-Methyl-2,4-pentanediol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Butanone, peroxide:

Remarks: This information is not available.

2-Methyl-2,4-pentanediol:

Remarks: This information is not available.

Reproductive toxicity

Not classified based on available information.

Components:**2-Butanone, peroxide:**

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity - Parent: NOAEL: 50 mg/kg body weight
Method: OECD Test Guideline 421
Result: negative

2-Methyl-2,4-pentanediol:

Effects on fertility : Species: Rat
Result: negative

STOT - single exposure

Not classified based on available information.

Components:**Hydrogen peroxide:**

Assessment: May cause respiratory irritation.

2-Methyl-2,4-pentanediol:

Remarks: No data available

STOT - repeated exposure

Not classified based on available information.

Components:**2-Methyl-2,4-pentanediol:**

Remarks: No data available

Repeated dose toxicity**Components:****2-Butanone, peroxide:**

Species: Rat
NOAEL: 200 mg/kg
Application Route: oral (gavage)
Exposure time: 28 d
Method: OECD Test Guideline 407

Hydrogen peroxide:

Species: Mouse
Application Route: Ingestion
Exposure time: 90 d
Symptoms: No adverse effects

2-Methyl-2,4-pentanediol:

Species: Rat

NOAEL: 450 mg/kg

Application Route: Ingestion

Method: OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 39 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Hydrogen peroxide:

| | |
|--|--|
| Toxicity to fish | : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : LC50 (Daphnia pulex (Water flea)): 2.4 mg/l Exposure time: 48 h |
| Toxicity to algae | : EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l Exposure time: 72 h NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l Exposure time: 72 h |
| Toxicity to microorganisms | : EC50 : Method: OECD Test Guideline 209 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC: 0.63 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) |

2-Methyl-2,4-pentanediol:

| | |
|---|--|
| Toxicity to fish | : LC50 (Gambusia affinis (Mosquito fish)): 8,510 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): 5,410 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| Toxicity to algae | : EC50 (Pseudokirchneriella subcapitata (green algae)): 429 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 |

12.2 Persistence and degradability

Components:

2-Butanone, peroxide:

| | |
|------------------|--|
| Biodegradability | : Result: Readily biodegradable. Method: OECD Test Guideline 301D |
|------------------|--|

Hydrogen peroxide:

| | |
|------------------|----------------------------------|
| Biodegradability | : Result: Readily biodegradable. |
|------------------|----------------------------------|

2-Methyl-2,4-pentanediol:

| | |
|------------------|--|
| Biodegradability | : Result: Readily biodegradable. Method: OECD Test Guideline 301F |
|------------------|--|

12.3 Bioaccumulative potential

Components:

2-Butanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: < 0.3 (25 °C)

Hydrogen peroxide:

Partition coefficient: n-octanol/water : log Pow: -1.57
Remarks: Calculation

2-Methyl-2,4-pentanediol:

Partition coefficient: n-octanol/water : log Pow: -0.14

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : **An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.**

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
Dispose of in accordance with local regulations.

SECTION 14: Transport information

14.1 UN number

| | |
|------|-----------|
| ADN | : UN 3105 |
| ADR | : UN 3105 |
| RID | : UN 3105 |
| IMDG | : UN 3105 |
| IATA | : UN 3105 |

14.2 UN proper shipping name

| | |
|------|--|
| ADN | : ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S)) |
| ADR | : ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S)) |
| RID | : ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S)) |
| IMDG | : ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S)) |
| IATA | : Organic peroxide type D, liquid (Methyl ethyl ketone peroxide(s)) |

14.3 Transport hazard class(es)

| | |
|------|-------|
| ADN | : 5.2 |
| ADR | : 5.2 |
| RID | : 5.2 |
| IMDG | : 5.2 |
| IATA | : 5.2 |

14.4 Packing group

| | |
|------------------------------|------------------------------|
| ADN | |
| Packing group | : Not assigned by regulation |
| Classification Code | : P1 |
| Labels | : 5.2 |
| ADR | |
| Packing group | : Not assigned by regulation |
| Classification Code | : P1 |
| Labels | : 5.2 |
| Tunnel restriction code | : (D) |
| RID | |
| Packing group | : Not assigned by regulation |
| Classification Code | : P1 |
| Hazard Identification Number | : 539 |
| Labels | : 5.2 |
| IMDG | |

| | |
|--|--|
| Packing group | : Not assigned by regulation |
| Labels | : 5.2 |
| EmS Code | : F-J, S-R |
| IATA (Cargo) | |
| Packing instruction (cargo aircraft) | : 570 |
| Packing group | : Not assigned by regulation |
| Labels | : Organic Peroxides, Keep Away From Heat |
| IATA (Passenger) | |
| Packing instruction (passenger aircraft) | : 570 |
| Packing group | : Not assigned by regulation |
| Labels | : Organic Peroxides, Keep Away From Heat |

14.5 Environmental hazards

| | |
|---------------------------|------|
| ADN | |
| Environmentally hazardous | : no |
| ADR | |
| Environmentally hazardous | : no |
| RID | |
| Environmentally hazardous | : no |
| IMDG | |
| Marine pollutant | : no |

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

| | | | |
|-----|--|--------------------|---------------------|
| P6b | SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES | Quantity 1 50 t | Quantity 2 200 t |
|-----|--|--------------------|---------------------|

Other regulations : Gefahrengruppe nach § 3 BGV B4: Ib (German regulatory requirements)

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

AICS (AU) : On the inventory, or in compliance with the inventory

NZIoC (NZ) : On the inventory, or in compliance with the inventory

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : On TSCA Inventory

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H242 : Heating may cause a fire.

H271 : May cause fire or explosion; strong oxidizer.

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Org. Perox. : Organic peroxides

Ox. Liq. : Oxidizing liquids

Skin Corr. : Skin corrosion

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN